

Liquid Paraffin LD-20

Technical white mineral oil (liquid paraffin), industrial grade. Clear, transparent, colourless, odourless.

Typical Properties

Property	Specification	Test Method
Appearance	Clear, transparent, colourless	Visual
Kinematic Viscosity @ 40 °C	18 - 22 cSt	ASTM D-445
Colour	min +30 Saybolt	IP 17
Density @ 15 °C	0.810 - 0.850 g/cm3	ASTM D-1298
Pour Point	max +5 °C	ASTM D-97
Flash Point	min 190 °C	ASTM D-92
Acidity or Alkalinity	passes	BP
Odour	Odourless	BP

Typical Applications

Textile spin finishes and fibre lubrication, PVC and plastics processing, rubber processing and extender oil, mould release agents, metalworking and general industrial lubrication, lamp oil, wax emulsions and polish formulations.

Packing

180 kg net steel drums. Other packing options available on request.

Storage & Handling

Store in tightly closed original containers in a dry, ventilated area away from direct sunlight and heat sources. Shelf life: 36 months from production date.

Application suggestions are indicative; final suitability for a specific process or product is to be validated by the customer. This product is not certified for food, cosmetic or pharmaceutical use unless separately documented. The values above are guaranteed specification limits. A batch Certificate of Analysis with measured results accompanies every shipment. Independent pre-shipment inspection (e.g. SGS) is available on request.