

Paraffin Wax L02

Semi-refined solid paraffin wax, heavy grade, low oil content and low ash. Slabs.

Typical Properties

Property	Specification	Test Method
Oil Content	1.5 - 2.0 %wt	ASTM D-721
Melting Point	60 - 68 °C	ASTM D-87
Kinematic Viscosity @ 100 °C	6.0 - 7.5 cSt	ASTM D-445
Colour	max 1.5	ASTM D-1500
Ash Content	nil	ASTM D-482
Total Acid Number	nil	ASTM D-974
Soap Number	nil	supplier method

Typical Applications

Pillar and container candles, candle blends, hot-melt formulations, paper and packaging coatings, polishes and paste waxes, matches, rubber processing and general industrial applications.

Packing

5 kg slabs in carton boxes, approx. 25 kg net per carton, stacked and loaded on pallets.

Storage & Handling

Store in tightly closed original containers in a dry, ventilated area away from direct sunlight and heat sources. Shelf life: 36 months from production date.

Application suggestions are indicative; final suitability for a specific process or product is to be validated by the customer. This product is not certified for food, cosmetic or pharmaceutical use unless separately documented. The values above are guaranteed specification limits. A batch Certificate of Analysis with measured results accompanies every shipment. Independent pre-shipment inspection (e.g. SGS) is available on request.