

Paraffin Wax L08

Light paraffin wax, low melting point. Semi-refined solid paraffin wax with white colour and high oil content. Slabs.

Typical Properties

Property	Specification	Test Method
Oil Content	max 8 %wt	ASTM D-721
Melting Point	52 - 55 °C	ASTM D-87
Penetration @ 25 °C	20 - 26 (0.1 mm)	ASTM D-1321
Colour @ 70 °C	max 0.5 (white)	ASTM D-1500

Typical Applications

Container candles, tealights and candle blends, wax emulsions for MDF / particleboard and chipboard, paper and packaging coatings, matches, firelighters and firelogs, polishes and paste waxes, rubber processing and general industrial applications.

Packing

5 kg slabs in carton boxes, approx. 25 kg net per carton, stacked and loaded on pallets.

Storage & Handling

Store in tightly closed original containers in a dry, ventilated area away from direct sunlight and heat sources. Shelf life: 36 months from production date.

Application suggestions are indicative; final suitability for a specific process or product is to be validated by the customer. This product is not certified for food, cosmetic or pharmaceutical use unless separately documented. The values above are guaranteed specification limits. A batch Certificate of Analysis with measured results accompanies every shipment. Independent pre-shipment inspection (e.g. SGS) is available on request.