

Paraffin Wax LP3

Light grade paraffin wax. Slabs 25 x 50 x 4 cm.

Typical Properties (Guaranteed Limits)

Property	Specification	Test Method
Oil Content	max 5.0 %wt	ASTM D-721
Melting Point	55 - 61 °C	ASTM D-87
Colour	reported on batch COA	ASTM D-156
Penetration @ 25 °C	18 - 23 (0.1 mm)	ASTM D-1321
Kinematic Viscosity @ 100 °C	3.6 - 4.4 cSt	ASTM D-445

Typical Applications

Tealights, grave / memorial lights, outdoor and garden candles, torches, firelighters and firelog production; board industry wax emulsions.

Packing

Slabs 25 x 50 x 4 cm packed in carton boxes, approx. 24 kg net per carton, stacked and loaded on pallets. Full truck load (FTL): 22 MT.

Storage & Handling

Store in a dry, ventilated area away from direct sunlight and heat sources. Keep cartons palletized; do not stack above supplier-marked limits.

Application suggestions are indicative; final suitability for a specific process or product is to be validated by the customer. This product is not certified for food, cosmetic or pharmaceutical use unless separately documented. The values above are guaranteed specification limits. A batch Certificate of Analysis with measured results accompanies every shipment. Independent pre-shipment inspection (e.g. SGS) is available on request. HS Code: 2712 20.