

Snow White Petroleum Jelly

Product Code: SSW2.AHT · Refined white petrolatum. White, soft, translucent semi-solid.

Typical Properties

Property	Specification	Test Method
Penetration @ 25 °C	120 - 140 (0.1 mm)	ASTM D-937
Colour (Lovibond, 1" cell)	0.5 Y - 0.7 Y	IP 17
Kinematic Viscosity @ 100 °C	5 - 7 cSt	ASTM D-445
Drop Melting Point	55 - 65 °C	ASTM D-127
Congearing Point	50 - 60 °C	ASTM D-938
Specific Gravity @ 25 °C	0.780 - 0.890	ASTM D-1298
Flash Point	min 200 °C	ASTM D-92

Typical Applications

Industrial lubricants, release agents, corrosion protection, cable filling compounds, leather and textile finishing, wax and ointment base formulations.

Packing

175 kg net drums. Other packing options available on request.

Storage & Handling

Store in tightly closed original containers in a dry, ventilated area away from direct sunlight and heat sources. Shelf life: 36 months from production date.

Application suggestions are indicative; final suitability for a specific process or product is to be validated by the customer. This product is not certified for food, cosmetic or pharmaceutical use unless separately documented. The values above are guaranteed specification limits. A batch Certificate of Analysis with measured results accompanies every shipment. Independent pre-shipment inspection (e.g. SGS) is available on request. HS Code: 2712 20.