

Residue Wax RW-1 (Foots Oil)

Residue wax / foots oil. High oil content petroleum wax stream for further processing and industrial use.

Typical Properties

Property	Specification	Test Method
Oil Content	min 8 %wt	ASTM D-721
Melting Point (cooling curve)	28 - 55 °C	ASTM D-87
Kinematic Viscosity @ 100 °C	3.9 - 12 cSt	ASTM D-7042
Colour	max 5.0	ASTM D-1500
Density @ 15.6 °C	0.80 - 0.88 g/cm3	ASTM D-4052
Flash Point (open)	min 200 °C	ASTM D-92

Typical Applications

Feedstock for wax de-oiling and refining, wax emulsions for MDF / particleboard and chipboard, firelighters and firelogs, rubber processing and extender applications, dust suppression, tarpaulin and paper impregnation, controlled release agent for chemicals and fertilizers.

Packing

1000 kg IBC or jumbo bag (FIBC), 175 kg steel drums, or bulk in heated tank.

Storage & Handling

Store in tightly closed original containers in a dry, ventilated area away from direct sunlight and heat sources. Shelf life: 36 months from production date.

Application suggestions are indicative; final suitability for a specific process or product is to be validated by the customer. This product is not certified for food, cosmetic or pharmaceutical use unless separately documented. The values above are guaranteed specification limits. A batch Certificate of Analysis with measured results accompanies every shipment. Independent pre-shipment inspection (e.g. SGS) is available on request.